Goecker for shooters

FUJINON XF 14MM F/2,8 Ø58

Varenummer: FUJIXF1428

6,156.00

DKK ex moms



FUJ!FILM

7,695.00

DKK incl moms

Produkteksperter:



Kenneth Lauritzen

kenneth@goecker.dk

35865126 København



Jakob Worr

kenneth@goecker.dk

35865142 Aarhus

Beskrivelse:

Fujinon XF 14mm f/2,8 R

- Wide angle f/2.8 prime (21mm full frame equivalent)
- Minimum focusing distance of just 18cm
- · Manual focus clutch for precise focusing
- 2 aspherical elements limit distortion and spherical aberrations
- 3 extra-low dispersion elements reduce color fringing and chromatic aberrations

Advanced optical design has been used to overcome the distortion-prone tendency of ultra wide-angle lenses to control distortion without digital correction. This contributes to achieving high resolution to all corners of this ultra wide-angle lens.

The lens structure consists of 10 elements in 7 groups, including 2 aspheric and 3 extra low dispersion elements, and a seven-blade rounded diaphragm.

The lens features distance and depth of field scales on the barrel, making it suitable for a range of shooting techniques such as prefocusing.

With the F2.8 wide open, the lens is suitable for low-light photography. The short minimum shooting distance of 18cm means it can effectively blur the background while also giving a sense of perspective characteristic to ultra wide-angle lenses.

The FUJIFILM X Mount's short back focus distance prevents vignetting to achieve clarity and brightness to all corners. Image distortion and chromatic aberration are well controlled to deliver high resolution to all corners of an image, making the lens perfect for landscape photography.

Goecker for shooters

Specifikationer:

Producent Fuji Kategori Objektiv Objektiv type Prime Brændvidde type Wide-angle Objektiv mount X (Fuji) Kompatible mounts X (Fuji) Fullframe Nej Macro Nej Billedestabilisator Nej Autofokus Ja Intern fokus Ja Modlysblænde Incl Linseelement / Gruppe 10/7 Nærgrænse 18 Største blænde F/2,8 Mindste blænde F/22 Brændvidde 14 Diameter 65 Længde 58.4 Filter diameter 58 Leverandør Fuji