

FUJINON XF 16-55MM F/2,8 R LM WR

Varenummer: FUJIXF165528



7,996.00

DKK ex moms

FUJIFILM

9,995.00

DKK incl moms

Produkteksperter:



Kenneth Lauritzen
kenneth@goecker.dk
35865126
København



Jakob Worre
kenneth@goecker.dk
35865142
Aarhus

Beskrivelse:

Fujinon XF 16-55mm f/2,8 R LM WR

- Versatile constant f/2.8 aperture, professional grade zoom lens
- 24-84mm (full frame equivalent)
- Three aspherical, three ED elements, multilayer HT-EBC coating, Nano GI coating
- Linear autofocus motor provides near silent, precise, fast focusing down to 0.02 seconds
- Dust- and moisture resistant construction, operable down to -10°C
- Rounded 9 blade diaphragm

The weather-resistant zoom lens XF 16-55mm F2.8 R LM WR is a flagship XF standard zoom lens with a focal length equivalent to 24mm to 84mm (35mm equivalent), and a constant f/2.8 aperture throughout the range. The advanced optical design controls various forms of aberration to achieve edge-to-edge sharpness across the entire zoom range.

A professional, large aperture zoom lens must produce stunning images and the XF 16-55mm uses nine-blade diaphragm to help minimize spherical aberrations.

Photography is all about compromise. Normally a zoom lens places greater emphasis on convenience at the sacrifice of quality. This lens has been designed with no compromise, so the image quality is comparable to that of a prime lens.

The lens is made of 17 elements in 12 groups, which includes three aspherical elements to reduce any distortion and spherical aberrations. In order to maintain edge to edge sharpness across the entire zoom range, three extra-low dispersion elements are also used which help to control chromatic aberrations.

Control the light

FUJIFILM's proprietary multilayer coating HT-EBC (High Transmittance Electron Beam Coating) is used to control ghosting and flares. Nano GI Coating is also used to reduce ghosting and flare from light coming at diagonal angles.

Capture every detail

The AF system is based on a high-speed linear motor which can focus as fast as 0.02 seconds. It's impossible to know when something dramatic is going to happen but you want to be ready when it does. This lens reacts as quick as you do when those precious moments occur.

Ready for all environments

Any professional walk around lens needs to be ready to go in all shooting conditions, especially adverse weather. The dust- and moisture-resistant construction of the lens allows you to immerse yourself in shooting, whatever the weather.

Specifikationer:

Producent	Fuji
Kategori	Objektiv
Objektiv type	Zoom
Brændvidde type	Normal
	Wide-angle
Objektiv mount	X (Fuji)
Kompatible mounts	X (Fuji)
Fullframe	Nej
Macronærgrænse	0.3
Macro	Ja
Billedestabilisator	Nej
Autofokus	Ja
Vejrbestandig	Ja
Intern fokus	Ja
Modlysblænde	Incl
Linseelement / Gruppe	17/12
Nærgrænse	0.6
Blændelameller	9
Største blænde	F/2,8
Mindste blænde	F/22
Brændvidde	16-55
Diameter	83.3
Længde	106
Vægt	655
Filter diameter	77
Leverandør	Fuji