

FUJINON XF 50-140MM F/2,8 R LM OIS WR

Varenummer: FUJIXF50140WR



10,396.00


DKK ex moms

FUJIFILM

12,995.00

DKK incl moms

Produkteksperter:



Kenneth Lauritzen

[kenneth@goecker.dk](mailto:kenneth@goecker.dk)

35 86 51 26

København



Jakob Worre

[kenneth@goecker.dk](mailto:kenneth@goecker.dk)

35 86 51 42

Aarhus

## Beskrivelse:

### ***Fujinon XF 50-140mm f/2,8 R LM OIS WR***

- Lightweight constant aperture f/2.8 stabilized telephoto zoom lens
- 76-213mm (full frame equivalent)
- Optical image stabilization with up to 5 stop reduction
- Six ED, one Super ED elements, Nano GI coating
- Tripple linear motors provides silent, precise, fast focusing
- Rounded 7-blade diaphragm
- Weather resistant structure, operable down to -10°C

A telephoto zoom offering the most frequently used telephoto focal lengths, equivalent to 76mm\* to 213mm\*, and a maximum aperture of F2.8.

It features the latest technology, including dust / water and low temperature resistance, a triple linear motor, and the world's top image stabilization technology in its class, so that users do not miss a shot in any conditions.

Its advanced performance makes it a perfect choice, not only for portraiture and snapshots, but also to capture fast-moving subjects in sports or wildlife photography, and for general outdoor nature photography.

\*35mm format equivalent.

### ***23 elements shape the light***

Designed for clarity and strong contrast, this lens captures every detail in each scene. The Nano GI (Gradient Index) coating reduces ghosting and lens flare when shooting into strong light.

The use of six ED lens elements including one Super ED (extra-low dispersion) lens minimises chromatic aberration to achieve a high level of image resolving power. The lens configuration and coating, has been applied to deliver clarity, free of dullness or haziness, allowing the photographer to capture what their eyes see.

### ***As quick as you***

This is neither a long-distance runner or a sprinter. The lens makes a dash from the minimum shooting distance to infinity, and back again repeatedly. There are three requirements. It must be fast, quiet and maintain balance across its zooming range and at any shooting distance, so as not to have any impact on your grip holding the lens. The balanced form eliminates camera shake for high-speed shooting.

### ***Time to take control***

The lens has five-stop image stabilisation inside, and can deliver up to six-stops when mounted on a camera with in-body image stabilisation. At the longest end of the zoom, 140mm, the slowest shutter speed when hand-holding should be 1/125 sec to avoid camera shake.

The OIS allows you to use a shutter speed of 1/4 sec! Concentrate on your subject and have the creative freedom to choose a wider range of shutter speeds. You can also benefit in low light, as you don't have to increase ISO sensitivity or rely on a tripod.

### ***Stay mobile***

Large-diameter zooms are typically very heavy, limiting where you can use the lens and what pictures you can take, however this lens weighs less than 1kg. After a day of shooting with the lens, when you head home and realise that there is no strain on your shoulders or arms, that is the moment you appreciate its true value.

### ***Ready for the elements***

Any professional lens needs to overcome all shooting conditions, especially adverse weather. The dust- and moisture-resistant construction of the lens allows you to immerse yourself in shooting, even during rain or sandy environments.

## Specifikationer:

Producent	Fuji
Kategori	Objektiv
Objektiv type	Zoom
Brændvidde type	Normal
	Tele
Objektiv mount	X (Fuji)
Kompatible mounts	X (Fuji)
Fullframe	Nej
Macronærgrænse	1
Macro	Ja
Billedestabilisator	Ja
Autofokus	Ja
Vejrbestandig	Ja
Intern fokus	Ja
Modlysblænde	Incl.
Linseelement / Gruppe	23/16
Nærgrænse	100
Blændelameller	7
Største blænde	F/2,8
Mindste blænde	F/22
Brændvidde	50-140
Diameter	82.9
Længde	175.9
Vægt	995
Filter diameter	72
Leverandør	Fuji