

GODOX VING 860II FLASH FOR NIKON

Varenummer: GODOXV860IIN



1,196.00

DKK ex moms



1,495.00

DKK incl moms

Produkteksperter:



Bjarne Blom

bjarne@goecker.dk

35865134

København



Bo Christensen

bjarne@goecker.dk

35865144

Aarhus

Beskrivelse:

Product Highlights

- Built-In 2.4GHz X Wireless Radio System
- Guide Number: 197' at ISO 100 and 200mm
- Zoom Range: 20-200mm (14mm with Panel)
- Tilts from -7 to 90°
- Rotates Left & Right 180°
- Wireless Master/Slave TTL Functionality
- Recycle Time: 1.5 Seconds at Full Power
- High-Speed, 1st and 2nd Curtain Sync
- Runs on Rechargeable Li-Ion Battery Pack

Power, speed, and integrated radio transmission make the VING V860IIC TTL Li-Ion Flash Kit from Godox a hard-to-beat option for your Canon cameras. Fully compatible with E-TTL / E-TTL II systems, the V860IIC supports many advanced functions and features. Also, it features the Godox 2.4GHz X wireless radio system which provides both master and slave TTL functionality with a range of up to 328'. On top of this, the flash is powerful and versatile, featuring a guide number of 197' at ISO 100 and 200mm along with a zoom range of 20-200mm, which can be expanded to 14mm with the use of the pull-out panel. And, this flash runs off a rechargeable Li-ion battery pack, that ensures fast recharge and long-lasting shoots.

For general operation, the V860IIC features full bounce flash capabilities, including tilting from -7 to 90° and rotation left and right 180°. As a E-TTL / E-TTL II-compatible unit, this flash offers support for high-speed sync, flash exposure compensation, 1st and 2nd curtain sync, and much more. Additionally, it can function as an optical master or slave unit if needed.

- The Godox 2.4GHz X wireless radio system has an impressive range of 328' along with the ability to choose between 32 channels and set up three groups. The system is compatible with Godox's X series or transmitters for more advanced functionality and setups.
- A powerful guide number of 197' at ISO 100 and 200mm ensures your subjects are properly illuminated.
- A zoom range of 20-200mm, as well as a wide-angle panel that supports 14mm, ensures maximum compatibility with a range of lenses and shooting styles.
- The flash head can tilt from -7 to 90° and rotate 180° both left and right for full bounce capabilities.
- Optical wireless transmission is available with access to four channels and three groups as well as a range of up to 49'.
- An AF assist light is present with a range of 2-32.8'.
- This flash supports various functions, including multi flash, high-speed sync, 1st and 2nd curtain sync, flash exposure compensation, and more.
- The 11.1V, 2000mAh Li-ion polymer battery pack included with the flash will provide recharge times of faster than 1.5 seconds and approximately 650 full-power flashes.
- In addition to the hot shoe and wireless triggering, the V860IIC offers a 2.5mm sync port for a wired connection to a camera or receiver.
- A micro-USB port is available for installing firmware updates.

Goecker for shooters

Specifikationer:

Producent	Godox
Kategori	Flash
Leverandør	Godox