

TOKINA 16-28MM T3 CINEMA E-MOUNT

Varenummer: TOK105441



22,864.00

DKK ex moms

28,580.00

DKK incl moms

Tokina

Produkteksperter:



Ronni Jaqué

ronni@goecker.dk

35865107

København



Jakob Worre

jakob@goecker.dk

35865142

Aarhus

Beskrivelse:

The highly innovative Tokina Cinema 16-28mm T3.0 has been re-engineered to meet the demanding needs of the professional cinematographer. Using the successful optical formula of the award winning still lens, Tokina engineers have created a lens that is Parfocal, has dramatically reduced breathing and image shift, and a de-clicked, 9-bladed, curved iris for beautiful bokeh and precise exposure control. With its 28cm close-focus capability, the lens allows you the freedom to capture a super wide-angle of view while still maintaining a tight perspective on your subject.

FEATURES:

- Full frame super-wide 16-28mm lens
- Parfocal lens design allows you to maintain precise focus while using the zoom control
- Fast constant T3.0 aperture throughout the 16mm to 28mm zoom range
- Reduced breathing so you can focus on the scene and not the lens
- Smooth, de-clicked, 9-bladed, curved iris for beautiful out-of-focus areas
- Virtually no image shift when using the zoom control during filming
- Aspherical elements and Super-Low Dispersion glass reduce distortion and increase optical performance
- 4K image ready
- Durable, all-metal cine-style housing with geared manual zoom, focus and aperture rings for use in follow-focus systems
- Common 114mm front diameter for use with a wide variety of matte boxes and accessories
- Zoom, focus, and iris marking are on both sides of the lens for easy viewing and more mounting/follow-focus options
- LDS (Lens Data System) support is possible

Specifikationer:

Producent	Tokina
Kategori	Objektiv
Objektiv type	Zoom
Brændvidde type	Wide-angle
Objektiv mount	E (Sony)
Kompatible mounts	E (Sony)
Fullframe	Ja
Special elementer/coatings	Asfæriske og Super-ow disperation elementer
Macro	Nej
Billedestabilisator	Nej
Autofokus	Nej
Linseelement / Gruppe	15/13
Maks synsvinkel	107.11 til 76.87°
Nærgænse	28
Blændelameller	9
Største blænde	T/3
Mindste blænde	T/22
Brændvidde	16-28
Diameter	123
Vægt	1500
Filter diameter	114